



CATÁLOGO CÂMARAS

Marcas: IRA, Tortuga, QBOM, Original, JFF e Buffalo



CONTEÚDO

Moto

página **3**

Carrinho de mão

página **4**

Linha Pesada

página **5**

Comercial Leve

página **6**

Agrícola

página **8**

Fora de Estrada

página **14**


Linha Industrial

página **16**

Linha Passeio

página **17**

Motocicleta



MI 0417	MI 0514	MI 0518	MI 0519
60/100-17	80/100-14	90/90-18	90/90-19
2.25-17	80/90-14	2.75-18	80/90-19
2.50-17	90/90-14	80/100-18	70/100-19
70/80-17	80/80-14	80/90-18	2.50-19
70/100-17	90/80-14	2.50-18	2.75-19
70/90-17	2.75-14	3.00-18	3.00-19
60/90-17	3.00-14	-	3.60-19
2-17	2 1/2-14	-	-
2 1/4-17	2 3/4-14	-	-
2 1/2-17	-	-	-

MI 0521	MI 0617	MI 0618
90/90-21	110/90-17	120/80-18
80/90-21	120/90-17	120/70-18
3.00-21	120/80-17	130/70-18
2.75-21	110/80-17	4.60-18
2.50-21	100/80-17	4.25-18
70/100-21	110/70-17	4.10-18
80/100-21	120/70-17	4.00-18
-	130/70-17	3.50-18
-	100/90-17	3.25-18
-	4.00-17	120/90-18
-	4.25-17	110/80-18
-	4.60-17	90/100-18
-	-	100/100-18
-	-	110/100-18
-	-	100/90-18
-	-	110/90-18
-	-	100/80-18

Carrinho de mão




Disponível em três marcas (Buffalo, QBOM, Original) com diferentes aplicações:

BUFFALO importada	QBOM nacional	ORIGINAL nacional
3.25-8	155/50-8 TR13	3.25-8 TR13
3.50-8	14.5x6.0-8 TR13	3.50-8 TR13
3.50-4	4.00-8 TR13	
4.00-8	5.00-8 TR13	




MEDIDA	VÁLVULA	APLICAÇÃO
10.00 R 20	TC 131	10.00 R 20 ; 10.00 - 20
		275 / 80 R 20
11.00 R 22	TC 131	11.00 R 22 ; 11.00 - 22
		10.00 R 22 ; 10.00 - 22
9.00 R 20	TC 131	9.00 R 20 ; 9.00 - 20
		8.25 R 20 ; 8.25 - 20
		11 / 80 R 20
295/80 R 22.5 C	TR 462 C	295 / 80 R 22.5
		315 / 80 R 22.5
		305 / 85 R 22.5
		295 / 75 R 22.5
		305 / 75 R 22.5
		315 / 75 R 22.5
		305 / 70 R 22.5
		315 / 70 R 22.5
		335 / 65 R 22.5
		11 R 22.5 ; 11 - 22.5
		12 R 22.5 ; 12 - 22.5
275/80 R 22.5 FC	TR 462 FC	255 / 80 R 22.5
		275 / 80 R 22.5
		265 / 75 R 22.5
		275 / 70 R 22.5
		305 / 60 R 22.5
		315 / 60 R 22.5
		9 R 22.5 ; 9 - 22.5
		10 R 22.5 ; 10 - 22.5
12.00 R 24	TC 131	12.00 R 24 ; 12.00 - 24
		12.00 R 25 ; 12.00 - 25
		11.00 R 24 ; 11.00 - 24
		325 / 95 R 24



QBOM

MEDIDA	VÁLVULA	APLICAÇÃO
LTQ 1215 (continua na próxima página)	TR 13	185 R 15 C
		185/80 R 15 C
		195/80 R 15 C
		205/80 R 15 C
		215/80 R 15 C
		LT 195/75 R 15
		LT 205/75 R 15
		LT 215/75 R 15
		LT 225/75 R 15
		LT 195/70 R 15
		LT 205/70 R 15
LTQ 1215 (continuação)	TR 13	LT 215/70 R 15
		LT 225/70 R 15
		195/65 R 15 C
		205/65 R 15 C
		215/65 R 15 C
		215/60 R 15 C
		225/60 R 15 C
		235/60 R 15 C
		6.70 - 15 LT
		7.00 - 15 LT
LTQ 1415	TR 13	LT 215/80 R 15
		LT 225/80 R 15
		LT 235/80 R 15
		LT 225/75 R 15
		LT 235/75 R 15
		LT 245/75 R 15
		LT 255/75 R 15
		LT 235/70 R 15
		LT 245/70 R 15
		LT 255/70 R 15
		LT 245/65 R 15
		245/60 R 15
		255/60 R 15
		29x9.50 R 15 LT
		30x9.50 R 15 LT
		7.00 - 15 LT
7.50 - 15 LT		



QBOM

MEDIDA	VÁLVULA	APLICAÇÃO
LTQ 1416	TR 13	LT 215/85 R 16
		LT 235/85 R 16
		LT 215/80 R 16
		LT 235/80 R 16
		LT 225/75 R 16
		LT 235/75 R 16
		LT 245/75 R 16
		LT 235/70 R 16
		LT 245/70 R 16
		LT 255/70 R 16
		245/65 R 17 C
		255/65 R 17 C
		7.00 - 16 LT
		7.50 - 16 LT

Tortuga

MEDIDA	VÁLVULA	APLICAÇÃO
CL 1416	TR 460 ou SC 84 ou SC 95	7.50 R 16 ; 7.50 - 16
		7.00 R 16 ; 7.00 - 16



Tortuga

MEDIDA	VÁLVULA	APLICAÇÃO
AG 1012	TR 15	5.00 / 6 - 12
		5.00 - 12
		6 - 12
		170 / 80 - 12
		23 x 8.50 - 12
		6.5 / 80 - 12
AG 0921	TR 35	4.50 - 21
		4.75 / 5.00 - 21
		5.25 / 5.50 - 21
AG 1216	TR 15	6.00 - 16
		6.50 - 16
		7.00 - 16
		7.5 L - 15
		180 / 90 - 16
		190 / 90 - 16
		200 / 90 - 16
		210 / 80 - 16
		230 / 70 - 16
		9.0 / 70 - 16
		7 - 16
AG 1616	TR 15	8.25 - 16
		9.00 - 16
		11 L - 16
		11.5 / 70 - 16
		10.5 / 65 - 16
		250 / 80 R 16
		270 / 75 R 16
		280 / 70 R 16
		300 / 70 R 16
		300 / 65 R 16
		9.5 - 16
		280 / 60 - 15.5
		260 / 70 R 16.5
		10 - 16.5



Tortuga

MEDIDA	VÁLVULA	APLICAÇÃO
AG 1916	TR 15	10.00 - 16
		11.00 - 16
		12.5 L - 16
		360 / 65 R 16
		13.0 / 75 - 16
		14.0 / 65 - 16
		12.4 - 16
		320 / 70 R 16.5
		12 - 16.5
AG 1915	TR 15	11 L - 15
		12.5 L - 15
		10.00 - 15
		320 / 60 - 15
		380 / 60 - 15
		400 / 50 - 15
		31 x 12.50 - 15
		31 x 13.50 - 15
		31 x 15.50 - 15
		33 x 12.50 - 15
		10.5 / 85 - 15.3
		11.5 / 80 - 15.3
		12.5 / 80 - 15.3
		300 / 80 - 15.3
		320 / 80 - 15.3
AG 2018	TR 15	260 / 70 - 15.3
		12.5 / 80 - 18
		320 / 80 R 18
		320 / 65 R 18
		340 / 65 R 18
		12.0 / 75 - 18
		13.0 / 65 - 18
		360 / 70 R 17.5
		400 / 55 - 17.5
		36 x 16 - 17.5
14 - 17.5		



Tortuga

MEDIDA	VÁLVULA	APLICAÇÃO
AG 2730	TR 218 A	16.9 R 28 ; 16.9 - 28
		16.9 R 30 ; 16.9 - 30
		14.9 R 30 ; 14.9 - 30
		420 / 90 R 30
		380 / 85 R 30
		420 / 85 R 30
		420 / 80 R 30
		420 / 70 R 30
		16.5 / 85 R 30
		17.0 - 30
		420 / 85 R 28
		440 / 80 R 28
		480 / 75 R 28
		480 / 70 R 28
		500 / 70 R 28
		520 / 70 R 28
		480 / 65 R 28
		540 / 65 R 28
520 / 60 R 28		
16.5 / 85 - 28		
17.0 - 28		
AG 2428	TR 218 A	14.9 R 28 ; 14.9 - 28
		14.9 R 26 ; 14.9 - 26
		13.6 R 28 ; 13.6 - 28
		380 / 85 R 28
		420 / 75 R 28
		380 / 70 R 28
		420 / 70 R 28
		440 / 65 R 28
15.0 - 28		





Tortuga

MEDIDA	VÁLVULA	APLICAÇÃO
AG 2824	TR 218 A	16.9 R 24 ; 16.9 - 24
		14.9 R 24 ; 14.9 - 24
		17.5L R 24 ; 17.5L - 24
		420 / 85 R 24
		440 / 80 R 24
		480 / 75 R 24
		445 / 70 R 24
		460 / 70 R 24
		480 / 70 R 24
		500 / 70 R 24
		480 / 65 R 24
		16.5 / 85 - 24
		48 x 20.00 - 24
		500 / 60 - 22.5
		550 / 60 - 22.5
		560 / 60 - 22.5
		600 / 50 - 22.5
		16.5 / 70 - 22.5
600 / 50 - 24.5		
AG 3030	TR 218 A	18.4 R 30 ; 18.4 - 30
		16.9 R 30 ; 16.9 - 30
		18.4 R 28 ; 18.4 - 28
		420 / 90 R 30
		460 / 85 R 30
		480 / 70 R 30
		520 / 70 R 30
		540 / 65 R 30
600 / 55 - 30.5		





Tortuga

MEDIDA	VÁLVULA	APLICAÇÃO
AG 2424	TR 218 A	14.9 R 24 ; 14.9 - 24
		13.6 R 24 ; 13.6 - 24
		380 / 85 R 24
		400 / 80 R 24
		380 / 75 R 24
		380 / 70 R 24
		400 / 70 R 24
		420 / 70 R 24
		440 / 70 R 24
		440 / 65 R 24
		15.5 / 80 - 24
		15.0 - 24
		AG 1718
11.5 / 70 - 18		
250 / 80 R 18		
280 / 80 R 18		
280 / 70 R 18		
300 / 70 R 18		
300 / 65 R 18		
320 / 65 R 18		
AG 1616	TR 15	8.25 - 16
		9.00 - 16
		11 L - 16
		11.5 / 70 - 16
		10.5 / 65 - 16
		250 / 80 R 16
		270 / 75 R 16
		280 / 70 R 16
		300 / 70 R 16
		300 / 65 R 16
		9.5 - 16
		280 / 60 - 15.5
		260 / 70 R 16.5
10 - 16.5		





Tortuga

MEDIDA	VÁLVULA	APLICAÇÃO
AG 3530	TR 218 A	23.1R 30 ; 23.1-30
		21L - 30
		600 / 70 R 30
		600 / 65 R 30
		600 / 60 R 30
		620 / 60 R 30
		21L - 28
		540 / 75 R 28
		600 / 70 R 28
AG 3530 (* Continuação)	TR 218 A	620 / 70 R 28
		600 / 65 R 28
		650 / 65 - 30.5
		600 / 60 - 30.5
		620 / 60 - 30.5
		620 / 55 - 30.5
		650 / 55 - 30.5
		710 / 50 - 30.5
750 / 45 - 30.5		





Tortuga

MEDIDA	VÁLVULA	APLICAÇÃO
FE 2525*	TR 220 A	14.00 R 24 ; 14.00 - 24
		14.00 R 25 ; 14.00 - 25
		13.00 R 24 ; 13.00 - 24
		13.00 R 25 ; 13.00 - 25
		15.5 R 25 ; 15.5 - 25
		385 / 95 R 24
		385 / 95 R 25
		365 / 80 R 24
		395 / 80 R 25
		405 / 80 R 25
		17 / 80 R 24
FE 2725**	TR 220 A ou TRJ 1175 C	17.5 R 25 ; 17.5 - 25
		14.00 R 24 ; 14.00 - 24
		14.00 R 25 ; 14.00 - 25
		385 / 95 R 24
		385 / 95 R 25
		445 / 80 R 25
		445 / 70 R 24
		445 / 70 R 24
20 / 65 R 25 ; 20 / 65 - 25		
FE 3926	TRJ 1175 C	23.5 R 25 ; 23.5 - 25
		20.5 R 25 ; 20.5 - 25
		18.00 R 25 ; 18.00 - 25
		21.00 R 25 ; 21.00 - 25
		505 / 95 R 25
		575 / 95 R 25
		525 / 80 R 25
		605 / 80 R 25
		625 / 70 R 25
		650 / 65 R 25
25 / 65 R 25 ; 25 / 65 - 25		



Tortuga

MEDIDA	VÁLVULA	APLICAÇÃO
FE 3026	TRJ 1175 C	20.5 R 25 ; 20.5 - 25
		16.00 R 24 ; 16.00 - 24
		16.00 R 25 ; 16.00 - 25
		445 / 95 R 25
		525 / 80 R 25
		495 / 70 R 24
		555 / 70 R 24
		555 / 70 R 25
		550 / 65 R 25
		22 / 65 R 25
		22 / 70 - 24





Tortuga

MEDIDA	VÁLVULA	APLICAÇÃO
AG 1216	TR 15	6.00 - 16
		6.50 - 16
		7.00 - 16
		7.5 L - 15
		180 / 90 - 16
		190 / 90 - 16
		200 / 90 - 16
		210 / 80 - 16
		230 / 70 - 16
		9.0 / 70 - 16
		7 - 16

JFF

MEDIDA	VÁLVULA	APLICAÇÃO
7.50-15 TR 75A	TR75a	7.50-15
6.00-9	JS2	6.00-9
6.50-10	TR244a	6.50-10
7.00-12	TR75a	7.00-12



MEDIDA	VÁLVULA	APLICAÇÃO
GR 13/14 (continua na próxima página)	TR 13	155 R 13 ; 155 R 14 165 R 13 ; 165 R 14 175 R 13 ; 175 R 14 185 R 13 ; 185 R 14 155/80 R 13 ; 155/80 R 14 165/80 R 13 ; 165/80 R 14 175/80 R 13 ; 175/80 R 14 185/80 R 13 ; 185/80 R 14 165/75 R 13 175/75 R 14 185/75 R 14 165/70 R 13 ; 165/70 R 14 175/70 R 13 ; 175/70 R 14 185/70 R 13 ; 185/70 R 14
GR 13/14 (continuação)	TR 13	175/65 R 13 ; 175/65 R 14 185/65 R 13 ; 185/65 R 14 195/65 R 13 ; 195/65 R 14 185/60 R 13 ; 185/60 R 14 195/60 R 13 ; 195/60 R 14 205/60 R 13 ; 205/60 R 14 5.60 - 13 6.40 - 13 5.90 - 14 165 - 13 ; 6.45 - 13 175 - 13 ; 6.95 - 13 165 - 14 ; 6.45 - 14 175 - 14 ; 6.95 - 14
GR 15	TR 15	155 R 15 165 R 15 175 R 15 185 R 15 5.60 - 15 5.90 - 15 6.40 - 15 165 - 15 ; 6.85 - 15



Tortuga

MEDIDA	VÁLVULA	APLICAÇÃO
Gr 15/16	TR13	155R15; 165R15 175R15; 185R15 185/70R15; 195/60R15; 175R16; 175/75R16; 175/70R16; 185/65R16; 195/65R16; 195/60R16; 205/60R16;

JFF

MEDIDA	VÁLVULA	APLICAÇÃO
9.00/10.00-16	TR15	2.65/2.55/2.45 Bobcat 10.5/12.5-16
FR15	TR13	5.60-15 165r15
KR15	TR13	7.60 - 15 7.75 - 15 8.25 - 15 F70 - 15
KR16	TR15	215/80R16; 195/75R16; 205/75R16; 215/75R16